

## **Long Road Racing**

2668 Peachtree Road, Statesville, NC 28625 (980) 223-8547 LongRoadRacing.com

## Global MX-5 Cup 5/16" Fuel Line Adaptor Installation Instructions, 18-0517-06-RED

**Note:** Long Road Racing is not responsible for the installation and maintenance of this fuel line adaptor. The end user is responsible for ensuring that all 3 rubber seals are in good working condition and that there are no leaks present.

**Safety**: Follow industry safety procedures to prevent fuel spillage when disconnecting fuel lines.

**Application:** This Fuel Line Adaptor is designed to add an 1/8" NPT Port on a 5/16" fuel line with a 7/16" dia retaining flange 3/4" from the end.

1. If you are using a new fully assembled Fuel Pump Out Kit, Mazda Motorsports part # 0000-06-5210 skip to step two. If you are replacing the fuel adaptor in an existing assembly, start by removing the hose with the dry-brake fitting from old fuel line adaptor and install it in the 1/8" NPT port on the new adaptor with thread sealer.





2. Unscrew the capture nut and remove the capture O-ring. Check inside the adaptor body to verify that the two O-rings inside are present, in good condition and located in the internal locating grooves.




Winning with Personal Service since 2001



## **Long Road Racing**

2668 Peachtree Road, Statesville, NC 28625 (980) 223-8547 LongRoadRacing.com

3. Slide the capture nut onto the fuel line. Lubricate the capture O-ring using a silicon O-ring lubricant, then slide the capture O-ring over the retaining flange on the fuel line as shown. The capture O-ring keeps the capture nut from passing back over the retaining flange.



4. Lubricate the outer surface of the fuel line with a silicon O-ring lubricant and then slide the Fuel Line Adaptor over the fuel line. Tighten Capture Nut to body and connect fuel line.



- 5. Turn power on vehicle and inspect for leaks. If no leaks are present start vehicle and inspect for leaks while running. <u>Do not continue use with any sign of leaks present.</u>
- 6. For Global MX-5 Cup ND Chassis, install Mounting Clip at engine lift hook as shown using factory bolt.





Winning with Personal Service since 2001